REMOTE CONTROL AOD PUMP RANGE

CRESTPUMPS
CHEMICAL PUMPING SOLUTIONS

AIR OPERATED DOUBLE DIAPHRAGM PUMPS

- IDEAL FOR PUMPING HIGH VISCOSITY LIQUID
- ATEX ZONE 1 & 2 CERTIFICATION
- IECEx CERTIFICATION
- CONTROLLED REMOTELY

Part of the **REMOTE CONTROL AOD** Pump Range

S-MBOX

S-CUBIC

S-MICRO

S-BOXER 7

S-BOXER 15

REMOTE CONTROL AOD OVERVIEW

The Crest Debem double diaphragm pumps of the RC line have been designed for all applications that require the pump to be controlled remotely or directly by the machine on which the pump is installed and are always operated with compressed air. They are ideal for pumping liquids with high viscosity, even if containing suspended solids.

All the remote controlled range are ATEX - IECEx certified, constructed in Polypropylene or PVDF in the plastic version or in aluminum or AISI 316 L for the metal versions. The vast range of materials available for the parts in contact with the fluid, such as pump casings and manifolds, diaphragms, balls, ball seats and o-rings, makes them compatible with any type of fluid present on the market.

Scan to see more of our Debem AOD Range

CRESTPUMPS

DEBEM
PUMP YOUR NEEDS

UK OFFICIAL DISTRIBUTOR

Tel: +44 (0)1425 627700
Email: info@crestpumps.co.uk
www.crestpumps.co.uk

REMOTE CONTROL AOD PUMP RANGE

CRESTPUMPS
CHEMICAL PUMPING SOLUTIONS

AIR OPERATED DOUBLE DIAPHRAGM PUMPS

S-MBOX

TECHNICAL SPECIFICATION

- Maximum flow rate: 6L/Min
- Suction/delivery connections: BSPP 1/4" f

	S-MBOX
Suction / delivery connections	BSPP 1/4" f
Air Fitting	BSPP 1/8 "f
Max. Flow rate	6 l/min
Max supply air pressure	8 bar
Max. negative suction head - dry running **	3m
Max negative suction head - pump primed	9.5m
Diameter max suspended solids	0mm
Noise Level	60 dB
Volume Stroke	3.2cc

S-CUBIC

TECHNICAL SPECIFICATION

- Maximum flow rate: 17L/Min
- Suction/delivery connections: G 3/8" f

	S-CUBIC
Suction / delivery connections	G 3/8 "f
Air Fitting	G 3/8"f
Max. Flow rate	17 l/min
Max supply air pressure	8 bar
Max. negative suction head - dry running **	3m
Max negative suction head - pump primed	9.5m
Diameter max suspended solids	0.5mm
Noise Level	65 dB
Volume Stroke	10.3 cc

Tel: +44 (0)1425 627700
Email: info@crestpumps.co.uk
www.crestpumps.co.uk